



# API-20

## Corrosion Inhibitor/Lubricant

### FEATURES

- Light, non-tacky film protection
- Displaces moisture
- Easy to clean
- Will not varnish
- Reduces bath contamination
- Lubricates
- Washes clean with warm water

### APPLICATIONS

- Designed to be compatible with PPG paint systems
- Used for short-term shutdown storage
- Protection from fumes, corrosion, dust contaminations

### DIRECTIONS

Metal Mates API-20 is supplied ready to use. Application rate should be approximately 150- 500 mg/sq. ft. depending on intended use. Re-application may be needed for long-term corrosion protection.

### HANDLING

Use appropriate safety equipment. Use with adequate ventilation. Avoid contact with eyes, skin and clothing. Keep away from extreme heat. Keep container closed when not in use.

### STORAGE

Store away from extreme heat, flame, or ignition sources. Pressure buildup may occur due to heat exposure or temperature change. Release pressure by slowly opening container.

### DISPOSAL

Absorb on suitable material and follow procedures listed below. Dispose of in a manner that is recommended by local, state, provincial and federal laws and regulations.



### PROPERTIES

<b>Appearance / Physical State</b>	liquid
<b>Odor</b>	petroleum odor
<b>Specific Gravity</b>	0.9
<b>Flash Point</b>	>230F (>110C)
<b>Boiling Point / Range</b>	>380F (>193C)
<b>Melting / Freezing Point</b>	<0F
<b>VOC Content</b>	>10
<b>Evaporation Rate</b>	<0.1
<b>Vapor Density</b>	Heavier than air
<b>Prop 65 Warning</b>	No
<b>Density</b>	7.5 lbs

### AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Color
MM4102	5 Gallon	Pail	1	Clear;Oily
MM4103	55 gal	drum	1	clear, oily
MM4106	330 Gallon	Tote	1	Clear;Oily



**CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved