

## HANDLING

- Avoid contact with skin, eyes and clothing. Keep away from open flames, hot surfaces and
- sources of ignition. Take precautionary measures against static discharges. Use only in an
- area containing flame proof equipment. Ensure adequate ventilation. To avoid ignition of
- vapors by static electricity discharge, all metal parts of the equipment must be grounded.
- Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld
- containers.

## STORAGE

- Keep away from open flames, hot surfaces and sources of ignition. Keep containers tightly closed in a cool, well-ventilated place. Keep out of the reach of children. Keep container closed when not in use. Keep away from incompatible materials.

## DISPOSAL

- Dispose of in accordance with local/regional/national regulations.

## FEATURES

- Ideal for transmission and engine marking that won't chip off
- Resistant to most coolants and cutting fluids
- Permanent ink writes on smooth surfaces such as metal, aluminum, steel, plastics, cardboard, and more
- Drying Time: 25 - 35 seconds



## PHYSICAL PROPERTIES

Appearance / Physical State	Liquid.
Odor	Mild. Pungent.
Flash Point	57°F to 60°F (14 - 15.6°C)
Boiling Point / Range	243°F (117°C)
VOC Content	86 - 89%
Evaporation Rate	> 1 (BuAc = 1)
Vapor Density	> 1 (air = 1)
Prop 65 Warning	Yes
Water Solubility	Moderate

## AVAILABLE IN

Color	Marker Tip	Units/Case	Part #
red	medium, felt (#38)	48	44819
yellow	medium, felt (#38)	48	44401
white	medium, felt (#38)	48	44175
green	medium, felt (#38)	48	44177
blue	medium, felt (#38)	48	44179
black	medium, felt (#38)	48	44203